



Test Report No. BTX 31850(2)/PS/05

Date: 7 February 2006

Page 1 of 2

Bute Fabrics Ltd 4 Barone Road Rothesay Isle of Bute Scotland PA20 0DP United Kingdom

Attention: Mr D. Graham

The following sample was submitted and identified by the client as:

Sample Description:

Sample of fabric no. CF750/Black 602 (Rosslyn) batch no. 17657/13

**Details of Sample:** 

Composition: 92% Pure New Wool/8% Nylon

Date Sample(s) Received:

21 December 2005

**Testing Period:** 

Tested between

21/12/05 and 09/01/06

Test(s) Requested:

Abrasion Resistance to BSENISO14465:2003 Annex A

**Test Results:** 

Detailed in Appendix A

**Comments/Conclusions:** 

The sample submitted meets performance level A of BS EN ISO

14465:2003 in respect of abrasion resistance (Annex A).

Signed for and on behalf of SGS United Kingdom Ltd

Paula Smith
Textile Technologist
Softlines Department

"This document is issued by the Company subject to its General Conditions of Service available on request and accessible at <a href="https://www.sgs.com">www.sgs.com</a>. Attention is drawn to the limitations of liability, indemnification and jurisdictional issues defined therein. Unless otherwise stated: (a) the results shown in this document refer only to the sample(s) tested and (b) such sample(s) are retained for 30 days only. This document cannot be reproduced except in full, without prior approval of the Company."

Tests denoted with an \* have been subcontracted to another UKAS Approved Laboratory. Tests marked [Non UKAS Accredited] in this Report/Certificate are not included in the UKAS Accredited Schedule for our Laboratory

Opinions and interpretations expressed herein are outside the scope of UKAS Accreditation

SGS United Kingdom Ltd

Oakwood House, City Road, Bradford BD8 8JY Tel +44 (0)1274 760400 Fax +44 (0)1274 760429 Registered in England No. 1193985 Rossmore Business Park, Ellesmere Port, Cheshire CH65 3EN www.sgs.com



## **Appendix A: Test Results**

<u>Martindale Abrasion Resistance</u> (EN 14465:2003-Annex A, based on BSENISO12947-2:1999) The test was conducted using a Martindale abrasion machine with a head loading of 12.0kPa, and the standard reference abradant fabric. The physically significant end point was taken as 3 or more threads broken though attention was paid to any relevant visual endpoint.

Specimen	Cycles to physical end point		Requirement
1	>100,000		-
2	>100,000		
3	>100,000		~
4	>100,000		
Mean	>100,000		
Lowest result	>100,000	*	≥35,000 (Level A)
Colour change after 3,000 cycle	es: 4-5		≥3

\*\*\* End of Report\*\*\*